

Aluminum window, door and facade systems, made to your drawings.

Every opening on the job is engineered, made and delivered as one package, to the sizes on your elevations. Nothing is stock. Manufactured in Türkiye to European standards and shipped direct to your site. No distributor and no dealer margin between you and the company that carries the warranty.

THE SYSTEMS

Windows	Casement, tilt-and-turn, awning and fixed lights, combined in one frame.	Sash to 47 × 94 in (1200 × 2400 mm), 330 lb · frame 3 3/8 in (85 mm)
Sliding, minimal frame	Large glass with almost nothing between the panes. Flat or floor-recessed track.	Sash to 108 sq ft (10 m²), 880 lb · 1 in (25 mm) visible at the interlock
Lift & slide	The whole-wall opener. All-glass and 90° corners with no structural post.	Sash to 118 × 118 in (3000 mm), 880 lb · flat ramp track available
Folding	Up to 14 leaves, seven each way, opening in or out. Corner with no column.	Leaf to 47 × 118 in (1200 × 3000 mm), 265 lb · 15/16 in (24 mm) ramp
Entrance and pivot	Around 90 face designs in the model book; six pivot designs, onyx and veneer among them.	Pivot sash to 990 lb (450 kg) · 3- and 5-point locking · sizes per project
Curtain walling	Pressure-plate or structurally glazed. Fixed fields and opening sashes read alike outside.	1 3/8 in (35 mm) sightline · glass 1/4 to 1 7/8 in · column to 7 1/4 in

GLASS

Double or triple, made in the manufacturer's own glass plant. Low-E, solar Low-E, laminated, tempered, frosted, tinted, curved, switchable. Integral blinds between the panes. Recent US houses go out as **1/4 in tempered + 5/8 in argon + 1/4 in tempered solar Low-E** (6+16+6 mm).

FINISH

Any RAL powder coat, a different color inside and out if the elevations ask for it, 14 wood-texture decors, anodized. Most modern work goes out black, RAL 9005.

HARDWARE

European throughout: hinges, handles, turning gear. Multipoint locking on doors, concealed hinges to 180°, insect screens on opening units. Keypad, fob and phone locks available on entrance doors.

TESTED PERFORMANCE: EUROPEAN CLASSES, PRINTED AS EUROPEAN

Air permeability EN 12207 to class 4 · Water tightness EN 12208 to class 9A · Wind resistance EN 12210 to class B4 / C2 · Acoustic EN ISO 10140 to 45 dB Rw · Burglar resistance EN 1627 to class RC3 · Frame U-value (U_f) EN ISO 10077 from 1.4 W/m²K

WHAT WE WILL NOT PRINT UNTIL WE CAN STAND BEHIND IT

PERFORMANCE IN US TERMS

European classes, printed as European. **US testing is being arranged.** Until an accredited US laboratory issues a report we will not give you an NFRC U-factor, an SHGC or a design pressure. What each system holds is put in writing before you order.

WARRANTY

Yakaza USA carries it. Not the manufacturer, not the installer. The term and what it covers are stated in your quote.

LEAD TIME

Confirmed in writing for your project, in the quote. We do not print a program on a sheet that we have not confirmed for the job in front of us.

INSTALLATION

Not included. It runs under a separate contract with an installer, and we tell you who.

Send the window and door schedule from your drawing set. The A-6 sheet is usually the whole brief. You get a price and a delivery date back, and one project manager in New York from that point to the last snag. You never deal with the factory.